

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A probe assembly for use in the extraction of analytes from a sample, which probe includes an elongate cylinder portion which is arranged to rotate about its ~~a~~ longitudinal axis of the elongate cylinder portion, and having thereon one or more ~~vanes~~ veins extending away from the cylinder portion, wherein the one or more vanes are coated with a solid phase as a means for extracting materials, and wherein the elongate cylinder portion is substantially hollow along its length to allow gas to flow therethrough.
2. (Cancelled)
3. (Currently Amended) A probe assembly according to claim 12, wherein the probe is shaped to maximise the area of the solid phase on the probe that is in contact with a liquid phase.
4. (Currently Amended) A probe assembly according to claim 1, further comprising an ~~wherein the extracting element, wherein the extracting element~~ is connected directly to a means of rotation, and/or the probe is arranged to be rotated in the sample.
5. (Currently Amended) A probe assembly according to claim 1, wherein the probe is arranged to be an impeller in the sample.
6. (Previously Presented) A probe assembly according to claim 1, wherein the probe includes a rotating device.

7. (Currently Amended) A probe assembly according to claim 1, wherein the one or more ~~vanes~~vein is are in the form of paddles, shoulders, or blades, extending from the cylinder portion.

8. (Currently Amended) A probe assembly according to claim 1, wherein the elongate cylinder and/or the ~~vanes~~veins are coated with a sorbent coating.

9. (Cancelled)

10. (Currently Amended) A probe assembly according to claim 19, wherein the hollow elongate cylinder includes one or more apertures or perforations, the apertures or perforations being arranged to permit gas to flow through the walls of the cylinder, or wherein the probe includes a sparger, to provide a diffuse stream of gas bubbles.

11. (Previously Presented) A probe assembly according to claim 1, wherein the probe further includes a sheath.

12. (Previously Presented) A probe assembly according to claim 11, which includes an elevation device arranged to move the elongate cylinder relative to the sheath.

13. (Previously Presented) A probe assembly according to claim 11, wherein an internal surface of the sheath and/or the elongate cylinder are coated.

14. (Previously Presented) A probe assembly according to claim 1, wherein the probe includes a heating device.

15. (Previously Presented) A probe assembly according to claim 1, which includes a housing having at least one inlet and at least one outlet arranged to permit entry and exit of gas to the probe assembly.

16. (Currently Amended) A probe assembly according to claim 7, wherein the one or more vanes is are arranged to extend substantially around the cylinder portion so as to form a spiral thread.

17. (Previously Presented) A probe assembly according to claim 8, wherein the sorbent coating comprises polymethylsiloxane, polyethylene glycol, silicone, polyimide, octadecylchlorosilane, polymethylvinyl chlorosilane, liquid crystal polyacrylates, grafted self organised monomolecular layers or inorganic coating materials.

18. (Previously Presented) A probe assembly according to claim 10, wherein the sparger comprises a sintered glass frit.

19. (Previously Presented) A probe assembly according to claim 11, wherein the sheath is arranged to pierce or penetrate a septum.

20. (Previously Presented) A probe assembly according to claim 3, wherein the shape causes movement within the liquid such that there is a continuous exchange of liquid in contact with the solid phase.